

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
14 February 2002 (14.02.2002)

PCT

(10) International Publication Number
WO 02/12833 A1(51) International Patent Classification⁷: G01D 11/02,
F16C 23/04, 27/02, 17/10

(21) International Application Number: PCT/GB01/03461

(22) International Filing Date: 1 August 2001 (01.08.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0019200.5 5 August 2000 (05.08.2000) GB(71) Applicant (for all designated States except US): REN-
ISHAW PLC [GB/GB]; New Mills, Wotton-under-Edge,
Gloucestershire GL12 8JR (GB).

(72) Inventors; and


(75) Inventors/Applicants (for US only): HUNTER, Stephen,

Paul [GB/GB]; 90 Cotswold Road, Chipping Sodbury,
Bristol, South Gloucestershire BS37 6DS (GB). REEVE,
Michael, Robert, John [GB/GB]; 27 Park Road, Malmes-
bury, Wiltshire SN16 0BX (GB). MCMURTRY, David,
Roberts [GB/GB]; Park Farm, Stancombe, Dursley,
Gloucestershire GL11 6AT (GB). DERRICK, Hugo,
George [GB/GB]; Ground Floor Flat, 1 Rockcliffe Av-
enue, Bathwick, Bath, Somerset BA2 6QP (GB).

(74) Agent: JACKSON, John, Timothy; Renishaw plc, Patent
Dept., New Mills, Wotton-Under-Edge, Gloucestershire
GL12 8JR (GB).(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK,
LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX,
MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL,
TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

[Continued on next page]

(54) Title: BEARING ARRANGEMENT



(57) Abstract: A bearing arrangement for an articulatable support (6) comprises bearing assemblies (20/28, 22/29, 24/30 and 26/32). In one embodiment the assemblies comprise a ball (20, 22, 24, 26) and aperture (40 figure 2) having sliding contact at discrete areas (36) during relative rotation. In another embodiment the sliding contact may be formed at a ball (20, 22, 24, 26) and a plastics e.g. P.T.F.E. support (84, 85 figures 10 and 11). Resilient displacement of the bearing contact along a rotational axis (A and B) is provided by planar spring supports (28, 32) and rigid support is provided by supports (29 and 30).

WO 02/12833 A1



(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *of inventorship (Rule 4.17(iv)) for US only*

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

Declarations under Rule 4.17:

- *of inventorship (Rule 4.17(iv)) for US only*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.